



XS30

Ideal Decorative Lighting

XS30 is a linear lighting system that can be implemented as both standalone luminaires and as continuous lines of light. It is perfect for decorative lines of light, wall grazing, or as a wall washer. Also available fully encapsulated to IP67, for outdoor or wet area applications.

A multitude of luminaire and mounting options make XS30 an exceptionally versatile lighting solution. An unrivalled range of light source options includes; static white, tunable white, dual tunable white, RGB, RGB+W, achieving up to 6000 lm/m light output and up to 33 W/m. Available in white, grey and black powder coat finish, as standard.

All light sources used for XS30 luminaires feature 3-step MacAdam LEDs to ensure excellent colour uniformity.



5-year
warranty




















Made in
Europe




NICHIA

Key Benefits

	High CRI80+, CRI90+, CRI95+		Stabilized current design
	3-step MacAdam LEDs		Customization for your project
	CCT: 2000K - 6500K		Efficacy up to 130 lm/W
	L90B10 60 000 hours		IP67
	Beam angle: 30°Lense+Louvre, 30° Lense, Microprism, Opal		Thermal resistance: -25° - +50°
	24V DC voltage input		Any Monoflex LED tape can be integrated inside the module
	Control sold separately; DALI, Casambi, 1- 10V, Phase Cut		Continuous line possibility
	Power: up to 33 W		Reverse voltage protection
	Available in 0.5 - 3m lengths		





Outdoor / Indoor

Emphasize architectural features of your building, highlight the walls in the office, illuminate artworks or living plants using the XS30 luminaire system.

By utilizing the vast customization options available for Venta luminaires, creating full-fledged professional lighting designs will be a breeze.


Housing colour




Painted black



Painted white



Anodized gray



Custom color – available on request

Luminaire types

Indoor


Continuous line possible for:
Indoor Microprism + White Optics,
Indoor Lens (+ Louvre optional)



Microprism



Lens



Lens + Louvre

Outdoor

Continuous line possible for:
Outdoor Opal



Microprism



Opal



Lens



Lens + Louvre





Options

Graze the walls to put focus on the unique textures and bring out character of the structure or wash the wall with light to hide imperfections and soften shadows.

Everything is possible with XS30.

Technical details

Light output

Lumen output: 4400 lm/m

Efficacy: up to 130 lm/W

Spectrum

Static white: 2000K / 3000K / 3500K / 4000K / 5000K / 5700K / 65000K
CRI80+ / CR90+ / CRI95+

Tunable white: 2000-6500K / Custom CCT range
CRI80+ / CR90+

RGB: R (Red) G (Green) B (Blue)

RGBW: RGB+2700-6500K / Custom CCT
CRI80+ / CR90+ / CRI95+

Optics

Lens + Louvre / Lens / Microprism / Opal


Feed cable

Single lead cable per luminaire

Profile colour:


Painted black, Painted white, Anodized gray,
Custom color – available on request

Sizes and Dimensions




Fix rotation angle: up to 200°

Minimum length 500mm (19.68in) - maximum length - 3000mm (118.11in)




Mounting Brackets



XS30-SMP

XS30-SMB

Angle Brackets




XS30-AMB1

XS30-AMB2

XS30-AMB3

Mounting Options


Universal Adjustable Mounting



Our experts will support you in implementing XS30 into your project to achieve the best results.

There are several factors to consider for wall washing and grazing applications: height of the wall, mounting type, wall-to-luminaire distance, luminaire placement angle.

Fixed Mounting




Housing colour


- Painted white
- Painted Black
- Stainless steel 316

Photometrics


Indoor:




14° Lens
Grazing light




14° Lens + UGR
Comfort grazing light



Microprism
For comfort
general lighting




30° Lens
Grazing light




30° Lens + UGR
Comfort grazing light


Outdoor:




14° Lens
Grazing light




14° Lens + UGR
Comfort grazing light




Microprism
For comfort
general lighting




30° Lens
Grazing light



30° Lens + UGR
Comfort grazing light



**Opal fully
encapsulated**
For continuous
light line effect



Opal
For continuous
light line effect

