


MONOLINE-XS3

A surface mounted extruded aluminium profile manufactured from high-density aluminium, with a highly durable anodised finish and opal (OC) diffuser.


MONOFLEX LED is available in static white, with a choice of Nichia (N175), Osram and Lumileds (D175) LED.

TECHNICAL

Housing:	Anodised Aluminium
Diffuser:	Polycarbonate UV Stabilised
Lengths:	2000mm & 3000mm
Max LED Wattage:	14.4w/m
Max PCB Width:	6mm
Hot-Spot Free:	≥175 LED/m
Weight:	0.12kg/m
IP Rating:	IP40



FINISH



CATALOGUE NO.

XS3-2-OC	2000mm anodised silver with opal diffuser
XS3-3-OC	3000mm anodised silver with opal diffuser

ACCESSORIES



▮ XS3-EC Aluminium end cap



▮ XS3-ECH Aluminium end cap with hole

MONOFLEX-PRO



Our professional-grade flexible LED tapes are manufactured in Europe using high-quality components from leading manufacturers.

Our Pro range (N-series) incorporates industry-leading LEDs from Nichia, providing exceptional performance: colour rendering, colour appearance, colour consistency, lumen output, and lumen maintenance.

N175



MONOFLEX-ECO



Our professional-grade flexible LED tapes are manufactured in Europe using high-quality components from leading manufacturers.

Our Eco range (D-series) features the PCB and electronic components of our Pro range (N-series), except for the LEDs, which are either Osram or Lumileds, depending on the colour temperature and colour rendering index.

D175



Disclaimer: Technical data is subject to change without prior notice. The data provided represent typical values. Due to tolerances in the production of components, and binning of LEDs, values for lumen output (Lm) and power (W/m) can vary by up to +/- 10%, whilst the colour temperature (CCT) can vary +/- 100°K. Electrical and thermal variation also influences the performance characteristics of LEDs.