

Cube round LED



Apparecchio a plafone a LED, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), orientabilità +/- 15°, alimentatore escluso.

Fixture-mounted unit, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), not adjustable, power supply excluded.

321.0022.01.20-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90, , max 350mA



321.0022.01.40-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90, , max 350mA



321.0022.01.4000-- for 4000°K



321.0022.01.2700-- for 2700°K

2 nero
black

4 bianco
white

Cube Square

CONFIGURA ONLINE
macrolux.store



Cube square LED



Apparecchio a plafone a LED, tolleranza colore 3 McAdams, gradi di emissione 20° (spot) oppure 40° (flood), orientabilità +/- 15°, alimentatore escluso.
Fixture-mounted unit, colour tolerance 3 McAdams, emission degrees 20° (spot) or 40° (flood), adjustability +/-15°, power supply excluded.

321.0023.01.20.-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90, , max 350mA



321.0023.01.40.-- 2 4
6w, 3000°K, 615lm, 102,5lm/w, CRI>90, , max 350mA



321.0023.01.4000.-- for 4000°K
321.0023.01.2700.-- for 2700°K

2 nero
black

4 bianco
white