


MD_45 wall

CONFIGURA ONLINE
macrolux.store



Peso / Weight 1,85 kg/m

MD_45, wall



Apparecchio parete pronto all'uso, completo di diffusore opale (efficienza 64%) o prismaticizzato trasparente (efficienza 92%), testate di chiusura e kit LED, driver incluso.

Already made wall fixture, complete with opal diffuser (efficiency 64%) or prismatic transparent (efficiency 92%), end caps and LED kit, driver included.

134.1145.1520.--	92 94 98	Opal diffuser
134.11459.1520.--	92 94 98	Prismatic screen
L=1520mm, 60w Upper LED, 29,4w, 24V, 3000°K, 3360lm, CRI>90, IP20 Lower LED, 30,5W, 3000°K, 4250lm, CRI>90, IP20,		
134.1145.1820.--	92 94 98	Opal diffuser
134.11459.1820.--	92 94 98	Prismatic screen
L=1820mm, 72w Upper LED, 35,3w, 24V, 3000°K, 4032lm, CRI>90, IP20, Lower LED, 36,6W, 3000°K, 5100lm, CRI>90, IP20		
134.1145.2420.--	92 94 98	Opal diffuser
134.11459.2420.--	92 94 98	Prismatic screen
L=2420mm, 96w Upper LED, 47w, 24V, 3000°K, 5376lm, CRI>90, IP20, Lower LED, 48,8W, 3000°K, 6800lm, CRI>90, IP20\		

cod. 134.1145*.L.4000.-- per 4000°K

- 92 nero opaco
matt black
- 94 bianco opaco
matt white
- 98 alluminio satinato anodizzato
satin anodized aluminum

