



Spot zero 80 led



2 nero opaco
 matt black

Proiettore LED, completo di alimentatore e connessioni, tolleranza colore 3 McAdams.
LED projector, complete with driver and connections, color tolerance McAdams 3.

265.0060.01.20.-- 2 (20°
6w, 3000°K, 615lm, 102lm/w, CRI>90,

265.0060.01.34.-- 2 (40°
6w, 3000°K, 615lm, 102lm/w, CRI>90,

cod. 265.0060.01.2700.(X°).-- per 2700°K
cod. 265.0060.01.4000.(X°).-- per 4000°K

265.0060.02.20.-- 2 (20°
9w, 3000°K, 1025lm, 114lm/w, CRI>90,

265.0060.02.34.-- 2 (34°
9w, 3000°K, 1025lm, 114lm/w, CRI>90,

cod. 265.0060.02.2700.(X°).-- per 2700°K
cod. 265.0060.02.4000.(X°).-- per 4000°K

Spot zero 80, 9w DALI



265.0060.08.(°K).(X°).--
9w, 1025lm, 114lm/w, CRI>90,

spot led without driver to customize



Driver da aggiungere separatamente.
Driver to be added separately.

265.0060.03.20.-- 2 (20°
9w, 3000°K, 1025lm, max 500mA, 114lm/w, CRI>90,

265.0060.03.34.-- 2 (34°
9w, 3000°K, 1025lm, max 500mA, 114lm/w, CRI>90,